
FRANCE

P5KA2NG-2U ServiceMaster



Universal Replacement Service Units

*Ever wish you
had 8 arms?
With the "ServiceMaster"
you only need 2!*



- ◆ **True 30mA Output-** The "ServiceMaster" can replace 8 ratings.
- ◆ **Diagnostic Circuit-** "Led" indicates the reason for service, allowing for quick, easy troubleshooting.
- ◆ **Primary Wiring Requirements of a Non-SCGFP -** with the added safety of Secondary Ground Fault Protection.
- ◆ **Service Button -** For easy troubleshooting of ground faults and primary wiring problems. Overrides the SCGFP for up to 30 minutes.
- ◆ **Auto Reset -** After secondary ground fault, automatically attempts to reset three times within ten seconds. Manual reset possible at any time by disconnecting primary power.
- ◆ **Secondary Circuit Ground Fault Protection - (SCGFP)** Disables unit upon detection of arcs to ground in compliance with **UL2161** and **NEC** requirements.
- ◆ **Easy Wiring Methods -** Virtual Ground and Series Wiring Methods
- ◆ **User Friendly -** Adapts to most grounding situations.
- ◆ **Features Include-** Easy to carry handle; On/Off Toggle Switch; No transformer box required for interior installations.
- ◆ ***Can be used in flashing/dimming applications.**

*UL does not have listing requirements for transformers that are remotely dimmed or flashed.

www.franceformer.com

P5KA2NG-2U ServiceMaster

SERVICE MASTER	REPLACES
15030 P5KA2NG-2U	15000, 12000 & 10500 Volt
9030 P5KA2NG-2U	9000, 7500, 6000, 5000, 4000, 3000 & 2000 Volt

Diagnostic LED Operation

Steady On:
Unit is in Normal Operation.

Continuous Flashing:
Unit is in Service Mode.

Service Switch does not operate without proper grounding.

Pulses Indicates

- 1.....In 15 second Diagnostic or Auto Reset mode
- 2.....A Secondary Ground Fault exists.
- 3.....Unit is not Grounded or Input Neutral and Line are reversed.
- 4.....Input voltage exceeds 120% of rating.



NORMAL POWER FACTOR

Catalog Number	VAC	Hz	Secondary		Primary V.A.	Input Amps	Wt. Lbs.	Case Dimensions					
			Volts	mA				L	W	H	A	B	C
15030 P5KA2NG-2U	120	60	15000	30	510	4.25	25	13.35	4.50	7.47	10.87	12.21	3.00
9030 P5KA2NG-2U	120	60	9000	30	330	2.75	17	13.35	4.50	7.47	10.87	12.21	3.00
15030 P5KA2NG-2U	277	60	15000	30	530	1.90	25	13.35	4.50	7.47	10.87	12.21	3.00
9030 P5KA2NG-2U	277	60	9000	30	320	1.15	17	13.35	4.50	7.47	10.87	12.21	3.00

FRANCE

10/03/03

2268 Fairview Blvd ♦ PO Box 300 ♦ Fairview, TN 37062 ♦ voice 800-753-2753 ♦ fax 615-799-3199