

# Matthews Reducers

## Performance Characteristics

For best results it is imperative that the appropriate reducer be chosen for proper flow and leveling of any topcoat system. Refer to the proper Product Technical Bulletin for the specific color system or primer being used.

<b>CONVENTIONAL REDUCERS</b>	<b>Usage</b>	<b>Specialty Characteristic</b>
<b>6379SP</b>	MAP Satin MAP	Use in cool temperatures, 60 - 75°F (16 - 24°C), & on small parts where overspray is not an issue
<b>45 280SP</b>	MAP Satin MAP	Use in warm temperatures, 70 - 80°F (21 - 27°C)
<b>45 290SP</b>	MAP Satin MAP	Use in very warm temperatures, 75 - 85°F (24 - 29°C) to optimize gloss, flow and leveling
<b>6396SP</b>	MAP Satin MAP	Use in hot temperatures, 80°F (27°C) & above to optimize gloss, flow and leveling
<b>45 251SP</b>	MAP Satin MAP	Use to blend with other MAP Reducers for extreme temperature
<b>LOW VOC REDUCERS</b>		
<b>6300SP</b>	VOC MAP SVOC MAP	Use in cool temperatures, 60 - 75°F (16 - 24°C) for 3.5 VOC compliance
<b>6301SP</b>	VOC MAP SVOC MAP	Use in warm temperatures, 70 - 85°F (21 - 29°C) for 3.5 VOC compliance
<b>6302SP</b>	VOC MAP SVOC MAP	Use in hot temperatures, 80°F (27°C) & above for 3.5 VOC compliance
<b>EXEMPT REDUCERS</b>		
<b>6370SP</b>	VOC MAP SVOC MAP	Exempt Reducer for 2.8 VOC compliance Use in cool temperatures, 60 - 75°F (16 - 24°C)
<b>6371SP</b>	VOC MAP SVOC MAP	Exempt Reducer for 2.8 VOC compliance Use in warm temperatures, 70 - 85°F (21 - 29°C)
<b>6372SP</b>	VOC MAP SVOC MAP	Exempt Reducer for 2.8 VOC compliance Use in hot temperatures, 80°F (27°C) & above

The above information is based on controlled environmental testing. Results may and will vary based on climatic conditions such as humidity and atmospheric pressure.

# Matthews Reducers

---

**Important:**

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

---

**See Material Safety Data Sheet and Labels for additional safety information and handling instructions.**

---

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION - US (412) 434-4515; CANADA (514) 645-1320; MEXICO 01-800-00-21-400

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the general public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to Matthews Paint.

Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does Matthews Paint warrant freedom from patent infringement in the use of any formula or process set forth herein.

If you require technical assistance, please call us toll-free 800/323-6593.



**MATTHEWS PAINT**

*The World's Finest Coating For Architectural Signage*

LakeView Corporate Park • 8201 - 100th Street  
Pleasant Prairie, WI 53158-2201

Toll Free: 800/323-6593 • Wisconsin: 262/947-0700

Toll Free FAX: 800/947-0377 • FAX: 262/947-0444