

Sign and Scoreboard Lighting

Attachon Lampholders,
Medium Base
200W 250V
660W 250V



Sign and Scoreboard Lampholders

FEATURES

- Insulation displacement terminals for stranded wire.
- Lay in wire channels, 1/4 turn twist top speeds installation.
- One piece terminals and contacts. No rivets or eyelets to loosen due to heat.
- Sockets are molded of heat-resistant phenolic.
- 732 is weatherproof – suitable for outdoor use.
- Snap-in or screw-in panel mounting options.
- Keyed spring washer prevents rotation of socket after installation.

Medium Base Attachon

Rating	W	V	Description	Wire Range	Mounting	Catalog No.
660	250	250	Phenolic	#14 to #12	Hook	732
660	250	250	Phenolic	#14 to #12	No-Hook	732-1
660	250	250	Phenolic	#14 to #12	Snap-in	732-3
660	250	250	Phenolic	#18 to #12	Snap-in	4734-2
660	250	250	Phenolic	#14 to #12	Screws	734

Medium Base Attachon with Guard

Rating	W	V	Description	Wire Range	Mounting	Catalog No.
200	250	250	Phenolic Socket Yellow Guard	#18 to #12	Hook	1466Y*

*Not CSA certified



R-8 Lampholders

TESTING & CODE COMPLIANCE

- UL Listed, file E7430, UL 496 requirements
- CSA Certified, file 1739 (6231-07), Meet CSA requirements, C22.2 no. 43
- NOM Certified

MATERIAL CHARACTERISTICS
Temperature Rating:
-40°C to 65°C

