

1547 & 1548 Series

Recessed
Double
Contact
Lampholder
for 800 and
1500 mA
Lamps

High Output
Pedestal
Type



1547.1 Series



1547.2 Series



The 1547 and the 1548 series are virtually the same lamp holder except that the 1547 Series has a lamp-center-to-panel distance of .39" greater than the .1548 Series. The 1547 Series may be ordered with vertical contacts.

Specifications

Rating: 660 watts, 600 V

Listing: UL File No. E-13408; CSA File No. LR95423.

UL listed and CSA certified for outdoor use in enclosed signs and fixtures

Suitable for outdoor use when properly installed.

Mounting: Pre-assembled self-retaining 8/32 mounting nuts, with 8/32 x 1/2" screws supplied in bulk

Materials:

Housing: White urea

Contacts: Silver-plated phosphor bronze

Terminations:

Wire Fast: *Designed for 18 gage solid or stranded top-coated wire with a 3/8" strip*

Screw *Designed for 18 gage solid or stranded top-coated*

Terminal: *wire with a 3/8" strip*

Wire Leads: 9" (201.6mm) No. 18 AWG stranded and tinned, 3/8" strip standard.

Wire rated AWM 1000 V, 90°C (194°F). Wire rated AWM 1000 V, 90°C (194°F)