

582 & 583 Series

Recessed
Double
Contact
Lampholder
for 800 and
1500 mA
Lamps



.582.GDF
Back View, Recessing in
Channel



.583.GDF



Completely
isolates the
face of the
socket from
ground.

No metal clips means no corrosion or electrical grounding



.582.BB
Socket Sentry™
Translucent
Silicone and
Black Neoprene

The Socket Sentry™ when installed on the bottom of a vertically installed T12 fluorescent lamp with a Kulka 582 Series lampholder will provide a shield of the lampglass, lampbase and lampholder electrical connection from water-spray, condensation, leakage and dust.

Specifications

Rating: 660 watts, dual rated 600 V or 1000 V

Listing: UL File No. E-13408; CSA File No. LR95423.

UL listed and CSA certified for outdoor use in enclosed signs and fixtures

Mounting: Snap-In, Dead Front Design patented: #5,122,074

Materials:

Housing: White urea

Contacts: Horizontal or Vertical silver plated phosphor bronze, self wiping

Gasket: Blue silicone treated neoprene "O" ring

Terminations: 9" (201.6 mm) long, 18 AWG stranded and tinned leads, ½" stripped wire standard

Rated: AWM 1000 V, 90°C (194°F). Longer lead lengths are available, Consult Sales Department