

WESTRIM™

PRODUCTS

A FRANCE COMPANY

GTO-15 Hi-Flex Wire

CONDUCTOR:

Material: Bare Copper
 Size: 14 AWG
 Stranding: 19/.0147"
 O.D.: .074" nom.



INSULATION:

Material: Polyvinyl Chloride Blend
 Wall Thickness: .098"
 Color: Black, White or Gray
 O.D.: .265" +/- .005" nom.

250 Feet per Roll

- ◆ Rated for 15,000 VAC, 105° C
- ◆ Meets the construction requirements of Underwriters Laboratories Inc.® Standard UL 814 effective 8/1/99.
- ◆ Meets the construction requirements of Canadian Standards Association C22.2 No. 127.

Description	Part Number	Catalog Number	Packaging	Weight
Hi-Flex GTO 15 - Black	30062	GTOB14	250 ft/roll	12 lbs.
Hi-Flex GTO 15 - White	30063	GTOW14	250 ft/roll	12 lbs.
Hi-Flex GTO 15 - Gray	30064	GTOG14	250 ft/roll	12 lbs.
Hi-Flex MAX GTO 15 - Black	30076	GTOBM	150 ft/roll	12 lbs.
Hi-Flex MAX GTO 15 - White	30077	GTOWM	150 ft/roll	12 lbs.
Hi-Flex MAX GTO 15 - Gray	30078	GTOGM	150 ft/roll	12 lbs.
Ballast Wire (4 reels/box)	BW(color)		500 ft reels	44 lbs./box

www.westrimproducts.com

2268 Fairview Blvd PO Box 300 Fairview, TN 37062 voice 615-799-1204 fax 615-799-9670

GTO-15 Hi-Flex MAX Wire

CONDUCTOR:

Material: Bare Copper
Size: 14 AWG
Stranding: 19/.0147"
O.D.: .074" nom.



INSULATION:

Material: Polyvinyl Chloride Blend
Wall Thickness: .150"
Color: Black, White or Gray
O.D.: .373" +/- .005" nom.

150 Feet per Roll

- ◆ Rated for 15,000 VAC, 105° C
- ◆ Meets the construction requirements of Underwriters Laboratories Inc.® Standard UL 814 effective 8/1/99.
- ◆ Meets the construction requirements of Canadian Standards Association C22.2 No. 127.
- ◆ Meets the integral sleeving requirement of Underwriters Laboratories Inc.® Standard UL 814 effective 8/1/99.

Ballast Wire



14 AWG

Stranding: 19/.0147 (Bare Copper)

PVC Dual Rated, meets or exceeds UL and CSA Standards

Meets UL 1015; rated for 105 degrees C at 600 V

Meets UL 1032; rated for 90 degrees C at 1000 V

Nominal O.D.: .134"

10 Colors: Orange/Black, Blue/White, Yellow, Green, Orange, Blue, White, Red, Brown & Black



email: westrim@westrimproducts.com

Copyright 2001