

WESTRIMTM

PRODUCTS

A FRANCE COMPANY

PKTM Housings



PKHXP

Female Hex fitting contains internal threads



PKRGP

Male fitting contains external threads



PKHFP

Female Hex fitting contains internal threads



PKTM Plug

2 3/8" OD Flange provides option to mount very securely with 4 - .15" mounting holes located on a 2" diameter

- ◆ PKTM Housings provide the best way to penetrate walls for electrode connections
- ◆ Zinc plated steel and borosilicate glass construction
- ◆ 1-2-3 spring assembly facilitates easy GTO cable connection (included with PKTM Housings and also available as a service item – CAT# PK123)
- ◆ Includes NEW PKTM Plug to protect and prevent failure of GTO cable at the rear of the PKTM Housing (abrasion, insect and moisture deterrent) (PKTM Plug NOT sold separately) and proposal in UL879 would mandate protection at rear of PKTM Housing (New PKTM Plug is soft and pliable, same material as PKTM Silicone Cap)
- ◆ Rated for 7500 volt applications, including 15000 V mid-point referenced transformer installations
- ◆ For UL Wet Rating, PKTM Housings must be used with PKTM Silicone Caps (CAT# PKSC) placed over the end of PKTM glass insert to protect from rain, snow, dust and bugs

Description	Part Number	Catalog Number	Panel Hole	Packaging	Weight
PK TM 1/2" Hex Female Fitting w/ Plug	38074	PKHXP	1 3/8"	25 per box	12 lbs
PK TM 1/2" Hex Male Fitting w/ Plug	38075	PKRGP	1 3/8"	25 per box	12 lbs
PK TM 1/2" Hex Female Fitting w/ Flange & Plug	38076	PKHFP	1 3/8"	25 per box	13 lbs

www.westrimproducts.com

PK™ Housings



PKHX

Female Hex fitting contains internal threads



PKRG

Male fitting contains external threads



PKHFP

Female Hex fitting contains internal threads

2 3/8" OD Flange provides option to mount very securely with 4.15" mounting holes located on a 2" diameter

- ◆ PK™ Housings provide the best way to penetrate walls for electrode connections
- ◆ Zinc plated steel and borosilicate glass construction
- ◆ 1-2-3 spring assembly facilitates easy GTO cable connection (included with PK™ Housings and also available as a service item – CAT# PK123)
- ◆ Rated for 7500 volt applications, including 15000 V mid-point referenced transformer installations
- ◆ For UL Wet Rating, PK™ Housings must be used with PK™ Silicone Caps (CAT# PKSC) placed over the end of PK™ glass insert to protect from rain, snow, dust and bugs

Description	Part Number	Catalog Number	Panel Hole	Packaging	Weight
PK™ 1/2" Hex Female Fitting	38005	PKHX	1 3/8"	25 per box	11 lbs
PK™ 1/2" Reg. Male Fitting	38006	PKRG	1 3/8"	25 per box	11 lbs
PK™ 1/2" Hex Female Fitting w/ Flange	38042	PKHF	1 3/8"	25 per box	12 lbs

